



**Contractors & Industrial Supply Co., Inc.  
Electrode Handling Division**

1241 Foster Avenue

Nashville, TN 37210 U.S.A.

Phone: (615) 256-8658 Fax: (615) 256-1367

[www.electrode-handling.com](http://www.electrode-handling.com)

# CAPS & METAL LIFT PLUGS

SOCKET DIAMETER (Inches / mm)	PART NUMBER	WEIGHT	ESTIMATED MAXIMUM COLUMN WEIGHT - 3 1/3 ELECTRODES (pounds / kilograms)	THREADS PER INCH (25.4 mm)	CAPABLE ELECTRODE SIZES FOR PLUG OR CAP	MAXIMUM ELECTRODE WEIGHT (pounds / kilograms)
<b>CAPS</b>						
6 / 150	542-0608	13 lbs. / 5.9 kg	420 / 190.51	4	6	125 / 56.7
7,8 / 175, 200	002-0804	17 lbs. / 7.7 kg	770 / 349.26	4	8	230 / 104.33
9,10 / 225, 250	002-1094	25.5 lbs. / 11.6 kg	1170 / 530.7	4	10	350 / 158.76
12 / 300	002-1213	43.5 lbs. / 19.7 kg	1670 / 757.49	3	12	500 / 226.8
<b>PLUGS</b>						
3 1/8" / 79.38	000-0314	6 lbs. / 2.7 kg	340 / 340	4	5,125	100 / 45.34
3 5/8" / 92.08	000-0354	7 lbs. / 3.2 kg	420 / 190.51	4	6	125 / 56.7
4 1/4" / 107.95	000-0424	9 lbs. / 4.1 kg	600 / 272.51	4	7	180 / 81.65
4 13/16" / 122.24	000-0474	11.5 lbs. / 5.2 kg	770 / 349.27	4	8	230 / 104.33
5 1/2" / 139.7	000-0543	16.5 lbs. / 7.5 kg	1170 / 530.7	3	10	350 / 158.76
6 1/8" / 155.58	000-0613	17.5 lbs. / 7.9 kg	1170 / 530.7	3	10	350 / 158.76
6.975" / 177.17	000-0673	17.5 lbs. / 7.9 kg	1670 / 757.49	3	12	510 / 231.33
8 1/2" / 215.9	001-0843	32.5 lbs. / 14.7 kg	2300 / 1043.26	3	14	690 / 312.98
8 3/4" / 222.25	001-0864	37.5 lbs. / 17 kg	4070 / 1846.12	4	16	1220 / 553.28
9 1/2" / 241.3	001-0943	30.5 lbs. / 13.8 kg	5170 / 2345.07	3	18	1550 / 703.07
10 5/8" / 269.88	* 001-1054A	39 lbs. / 17.7 kg	6400 / 2902.99	4	20	1920 / 870.90
10 5/8" / 269.88	001-1054	59 lbs. / 26.8 kg	6400 / 2902.99	4	20	1920 / 870.90
10 3/4" / 273.05	001-1063	64 lbs. / 29 kg	6400 / 2902.99	3	20	1920 / 870.90
11 3/4" / 298.45	* 001-1163A	35 lbs. / 15.9 kg	8700 / 3946.25	3	22	2610 / 1183.88
11 3/4" / 298.45	001-1163	63 lbs. / 28.6 kg	8700 / 3946.25	3	22	2610 / 1183.88
11 3/4" / 298.45	* 001-1164A	35 lbs. / 15.9 kg	8700 / 3946.25	4	22	2610 / 1183.88
11 3/4" / 298.45	001-1164	63 lbs. / 28.6 kg	8700 / 3946.25	4	22	2610 / 1183.88
12 1/2" / 317.5	001-1244	66 lbs. / 29.9 kg	10330 / 4685.61	4	24	3100 / 1406.14
12 1/2" / 317.5	* 001-1244A	37.5 lbs. / 17 kg	10330 / 4685.61	4	24	3100 / 1406.14
14 3/4" / 374.65	* 001-1464A	50 lbs. / 22.7 kg	14220 / 6450.08	4	26, 28	4270 / 1936.84
16" / 406.4	* 001-1604A	87 lbs. / 39.5 kg	15660 / 7103.26	4	30	4700 / 2131.88
17" / 431.8	* 001-1704A	92 lbs. / 41.7 kg	17320 / 7856.22	4	32	5200 / 2358.68

\* Designates High Strength Aluminum Design (Lighter Overall Lift Plug Weight)



Safety Note! Aluminum Style Lift Plugs CANNOT Be Used To Remove HOT Electrodes!



Certified Member

CE Compliant Products